





**Double Steel Security Personnel Pedestrian Door - Industrial Grade Exterior
Outdoor Security Door - 1800mm w x 2035mm h**

£599.00



Select your door preference at checkout in the notes (as viewed from outside)



CUSTOMISE HEIGHT & WIDTH WITH WIND-OUT ADJUSTABLE INFIL / EXPANSION PANELS

**OPEN IN or OUT
ACTIVE LEAF LEFT or RIGHT**




FIXING KITS FOR MASONRY/BRICK, TIMBER OR METAL STEEL FRAME



3 x Dog Leg Security Bolts on Hinge Side for Extra Security

OPTIONAL WINDOW/LOUVRE VENT



SIDE / TOP EXPANSION INFIL PANELS TO COVER ANY APERTURE SIZE



Side & Top Frame Extenders (Wind out to suit any opening)



Pre-installed Gaskets on Both Door/Frame Saving Install Time




Pre-installed Fixing Tabs x 4 On Both Sides for Ease of Install



Pre-installed Fixing Tabs x 4 On Both Sides for Ease of Install



Built in Weep Holes with Optional Frame Knockouts





REVIEWS.io

www.thisiswholesale.co.uk Reviews

★★★★★
4.8 Rating 24 Reviews

96%
of reviewers recommend
www.thisiswholesale.co.uk

Company Reviews



Note: This is a universal door & the Active leaf (primary opening door) can be alternated by rotating the frame upside down 180°. The Active leaf is secured by handle and/or lock/key set. The passive leaf is secured by internal concealed flush bolts top & bottom which can be accessed after opening the primary leaf. the active leaf has door furniture only ie. handle, keyset, pushpad/bar etc.

[Looking for ungraded Ultra High Security / heavy Duty Steel doors with 12 Point / Multi point Locking?](#)

THIS IS  WHOLESALE

**STEEL SECURITY
PERSONNEL
PEDESTRIAN
DOOR**





5 COLOURS & 3 SIZES UK STOCK AVAILABLE

- RAL 9003 WHITE
- RAL 7016 ANTHRACITE GREY
- RAL 9005 JET BLACK
- RAL 6007 JUNIPER GREEN
- RAL 5005 SIGNAL BLUE

Powder coated both in & out.

-840mm W x 2035mm H

-940mm W x 2035mm H

-1040mm W x 2035mm H

SPECIFICATION SHEET

Door Frame Material	1.5mm Galvanised Steel
Door Frame Thickness	90mm
Door Leaf Material	Double skinned 0.7mm galvanised steel
Door Leaf Thickness	45mm
Clear Opening Size	1995mm H x 750mm/850mm/950mm W
U Value	1.6w/m ² k (50mm Mineral Wool Insulation)
Acoustic Value	32dBa
Hinges	4 Stainless steel hinges
Weather Seal	Full weather seal to all 4 sides of the frame
Hole Cut Out Size	2035mm H x 840/940/1040mm W





4 x heavy duty hinges that offer extra security



Full set of stainless steel handle & lock



3 sets of keys, single point locking mechanism



Full weather seal to all 4 sides of the frame

INSTRUCTIONS

Steel Personnel Pedestrian Door to fit 840mm x 2035mm opening

THIS IS WHOLESALE .CO.UK


4pm CUT OFF TIME.
NEXT DAY DELIVERY.
10% TRADE DISCOUNT

1




Fit door in the hole hinged in the correct orientation (NOTE door is universal, i.e. can be fitted hinged on the left or right, just rotate 180° to so hinged on the opposite side).

2



Once door is square & firmly in position, using the pre-drilled tabs, mark fixing positions on the building lining/frame & drill using suitable drill bit.


3



Optional: if ordered the extra add on vanity trim (not cover any caps/rods), this can be fitted on the opposite side & secured with suitable adhesive /mastic.


Use anchor bolts or suitable frame fixings to secure in place (washers are advised). NOTE - due to various types of frame being installed into i.e. brick, metal, timber, we are unable to supply the door with fixings.

4



The lock mechanism latch can now be rotated to suit your configuration i.e. hinged left side or hinged right side using a screwdriver as shown.

5



Insert the lock mechanism cassette into the door & secure with the 2 x M5 screws as shown.

6



The lock barrel is fitted with with thumb turn from the inside / key insert to the outside. Handle & cover plate secured with screws as shown.

**UNIVERSALLY
HINGED LEFT OR
RIGHT**

Simply rotate the door 180° to hinge on the opposite side. Hinged side you can select at the point of installation depending on the orientation of the install.

BOTH IN & OUT POWDER COATING IN 5 DIFFERENT COLOURS

RAL 7016 Grey



RAL 9003 White



RAL 9005 Black



RAL 6007 Green



RAL 5005 Blue



Installation

OPTIONAL WINDOW/LOUVRE VENT

UNIVERSALLY HINGED LEFT OR RIGHT. SIMPLY ROTATE THE DOOR 180° TO HINGE ON THE OPPOSITE SIDE. SIMPLY SELECT OPEN IN OUR OUT. HINGED SIDE YOU CAN SELECT AT THE POINT OF INSTALLATION DEPENDING ON THE ORIENTATION OF THE INSTALL.

Colours in Stock

Steel security door for outdoor/interior use - industrial-grade personnel door is the ideal Security Door for Garage, Warehouse, Shed, Industrial Unit, Shipping Container, Farm Barn - can be primed & painted any colour yourself) complete with outer frame, & optional stainless steel door handle & lock with internal thumb turn & 3 sets of keys, single point locking mechanism). **OPTIONAL POWDER COATED COLOURS (AT EXTRA COST)**

- RAL 9003 WHITE (painted both sides in/out)
- RAL 7016 ANTHRACITE GREY (painted both sides in/out)



Dimensions & Adjustable Side / Overhead Panels

Square Vision Panel Window Linear Vision Panel Window Louvre Vent
PLEASE NOTE - THIS IS ONE STANDARD SIZED 2035mm h x 1800mm wide - ITEM IS RECOMMENDED TO BE MEASURED, ORDERED AND INSTALLED BY A SUITABLE EXPERIENCED PROFESSIONAL AS WE DO NOT TAKE ANY LIABILITY FOR INCORRECT MEASUREMENTS. FULL TECHNICAL DRAWING WITH ALL DIMENSIONS IS BELOW & INSTALLATION INSTRUCTIONS.

FOR CUSTOM SIZES, PLEASE SEE OUR SIDE EXPANSION / EXTENSION PANELS THAT COME WITH WIND OUT LUGS ALLOWING EXTENSION OF BOTH SIDES AND HEADER SECTION FROM 10MM -100MM, THUS MAKING THIS DOOR SUITABLE FOR ALL SIZED APERTURES FROM 1800 - 1900mm WIDTH AND 2035MM TO 2100MM H. FUTHER CUSTOM SIZES MADE ON REQUEST. CONTACT US FOR A QUOTE

Stock Door Size	+ 35mm Side Panel	+ 55mm Side Panel	+ 35mm Header Panel	+ 55mm Header Panel
1800mm x 2035mm	1810mm - 1850mm	1850mm - 1900mm	2035mm - 2070mm	2070mm - 2090mm

Optional Accessories

Door Furniture - Range of door furniture to choose from

- Stainless Steel Handles both Sides + Thumb-turn Internal / Keylock External c/w 3 Keys
- Stainless Steel Handles both Sides + Keylock External c/w 3 Keys
- Matt Black Power Coated Handles both Sides + Thumb-turn Internal / Keylock External c/w 3 Keys
- Matt Black Power Coated Handles both Sides + Keylock External c/w 3 Keys
- Combination Keypad Keycode Lock External + handle internal
- WC Vacant / Engaged Bathroom Door Handle c/w Internal Thumb-turn
- Exit Door Push Lever PAD Internal / Blanks External
- Exit Door Push Lever PAD Internal / Key Access Device External
- Exit Door Push Lever BAR Internal / Blanks External
- Exit Door Push Lever BAR Internal / Key Access Device External

Louvre Vent + Vision Panels

Optional Add on 500mm x 300mm Louvre Vent or 400mm x 400mm / 220mm x 1500mm Vision Panels - SELF INSTALLATION / CUTTING REQUIRED (these are supplied with the door only for the customer to install) see instructions below for details. This add on is not pre-installed by ourselves and is only supplied with the door for the customer / installer to fit. Requires a competent and experienced installer, we accept no liability for mis-installation / mis-cutting or damage to product during installation. Frame powder coated both sides and will be sent the same colour as the door selected. Note, 150mm clearance must be left around all 4 sides of the door.

Trim Surround Cover (a type metal architrave cover to tidy up the installation / any gaps)

When you install the door, you will inevitably get a small gap between say the block work or timber and the steel frame of the door on the reveal. This can be filled with silicone or expanding foam etc. The Vanity surround trim cover as a 3 pc kit of Angled steel (the same material + powder coated the same colour as the door) which is inserted between wall and door and fixed, using the return edge to essentially hide or make good this gap, thus removing the need for silicone etc. to tidy up this edge. This is an optional aesthetic part, supplied in 3 pcs (ie. 2 legs, 1 header) which you can custom cut to size to suit your installation (note - we recommend cutting the header piece to size first, then inserting the legs to get a clean edge. The legs should cut to size at ground level.

Cill/Sill for Steel Security Door (Cill Plate)

- 150mm depth to suit most common door installations
- 10mm Rear lip to stop water ingress and not impede on threshold for low threshold doors
- Low Profile 2mm Thick plate so doesn't impact overall door height
- Pencil round Nose front so no sharp edges
- 1140mm Length - simply cut to size with chip saw / Angle grinder to suit your opening, ideally for all sizes or those with adjustable side panels
- Aluminium so won't rust after cutting
- Stocked in range of standard powder coated colours to match the stock door frames
-

Fixing Kit - Masonry, Timber or Steel (Self Drillers)

1 x Pozi PZ2 Drill bit head or Hex bit

9 x 100mm Frame fixings

1 x mini magnetic spirit level

15 x pack of plastic window/door packers - Mixed

80mm clear silicone sealant

9 x M8 washers

Technical Specifications

Door Frame Material	<i>1.5mm Galvanised Steel</i>
Door Frame Thickness	<i>90mm</i>
Door Leaf Material	<i>Double skinned 0.7mm galvanised steel</i>
Door Leaf Thickness	<i>45mm</i>
Door Leaf Core	<i>50mm Mineral Wool Insulation</i>
Actual Door Size	<i>1943mm x 750mm/850mm/950mm</i>
U Value	<i>1.6 w/m²k (50mm Mineral Wool Insulation)</i>
Acoustic Value	<i>32dBa</i>
Hinges	<i>4 Stainless steel hinges</i>

Eurocylinder
Lock *70mm (35 -*
Cylinder *35)*

Weight: 840mm 46kg / 940mm 49kg / 1040mm 52kg

Downloads[DOWNLOAD PDF TECHNICAL DRAWING / DIMENSIONS](#)[DOWNLOAD STEEL DOOR INSTALLATION INSTRUCTIONS / MANUAL](#)[DOWNLOAD INSTRUCTIONS MANUAL FOR SIDE/HEADER EXPANSION INFIL PANELS](#)[DOWNLOAD VISION GLASS PANEL / LOUVRE VENT INSTRUCTIONS](#)[DOWNLOAD FIRE EXIT PUSH PAD/BAR + OUTSIDE ACCESS DEVICE INSTRUCTIONS](#)[DOWNLOAD FIRE EXIT PUSH PAD/BAR + EXTERNAL BLANK INSTRUCTIONS](#)[DOWNLOAD DOOR EXTERNAL BLANK / BLANKING PLATE INSTRUCTIONS](#)

DOWNLOAD COMBINATION CODE HANDLE LOCK INSTALLATION INSTRUCTIONS text_phone 02920 099 098
sales@thisiswholesale.co.uk | <https://onlineb2b.co.uk/>

[DOWNLOAD HIGH SECURITY MULTI-POINT LOCKING INC. PAS24 & FIRE RATED STEEL DOOR INSTALLATION INSTRUCTIONS](#)

[DOWNLOAD WC VACANT/ENGAGED CONVERSION KIT INSTALLATION INSTRUCTIONS](#)

[DOWNLOAD MAINTENANCE MANUAL](#)

- *NOTE: due to manufacturing tolerances with regards to batch variation, we recommend ordering all coloured/powder coated doors for a project at the same time, from the same batch as we cannot be held responsible for any variation that occurs between batches.*
- *Must be installed by a competent persons, we are not able to train, teach any DIY enthusiast how to fit a door correctly. Whilst its not a difficult job, each individuals competency and skill set varies and thus professional knowledge is advised to fit this product correctly, safely and securely for normal operation.*
- *Note - door includes mechanical / moving parts such as lock mechanism, hinges, latches and as such requires regular maintenance and upkeep ion the form of regular lubrication/oil applying.*