

**\*\*CLEARANCE\*\* LED Wallpack - 90W  
10,800lm - 365mm x 235mm x 190mm - Die-  
cast aluminium Body with 5mm Glass -  
Replacement for 70W MHL Metal Halide  
Replacements Flicker Free**

**£90.00**

## Product Description

**\*\*CLEARANCE\*\* Stock - limited quantities - check before ordering. Order entire amount required first time as once sold, no more will be available as a discontinued product**

90W IP65 LED wallpack is a favourite of councils, schools and local authority, with an 5mm glass reflector and die-cast aluminium body for durability. Powder coated [fade and abrasion resistant, electrostatically applied, thermally cured, triglycidic isocyanurate (TGIC) textured polyester powder-coating] black finish for a classic luminaire design, whilst being up to 60% more energy efficient and fit-and-forget with a +50,000 hour rated lifetime. High operational efficacy of 120lm/W. IP65 sealed die-cast aluminium housing, hinged for ease of maintenance and installation, unit suitable for general purpose wall mount area and security lighting in a range of out-building applications such as public sector, walkways etc.

DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE

## text\_attributes

### PRODUCT INFORMATION

|                  |                                   |
|------------------|-----------------------------------|
| LED Type         | Epstar SMD2835 LEDs               |
| Warranty         | No warranty on clearance products |
| Part L Compliant | Yes                               |
| Dimensions       | 365mm x 235mm x 190mm             |
| Weight           | 3.95kg                            |
| Equivalent to    | 70W MHL Wallpack                  |

### TECHNICAL SPECIFICATIONS

|                       |               |
|-----------------------|---------------|
| Power Consumption     | 40W           |
| Input Voltage         | 100-280V AC   |
| Power Factor          | >0.95         |
| Operating Temperature | -20°C to 50°C |
| L70 Rated Lifetime    | +50,000hrs    |
| Ingress Protection    | IP65          |

## LUMEN PERFORMANCE

|                              |         |
|------------------------------|---------|
| Luminous Efficiency          | 120lm/W |
| Beam Angle                   | 140°    |
| CRI (Colour Rendering Index) | >80Ra   |
| Lumen Output                 | 4,800lm |

## AVAILABLE OPTIONS

|                                       |                         |
|---------------------------------------|-------------------------|
| Colour Temperature                    | Cool White (6500-7000K) |
| 3-Hour Emergency Version              | No                      |
| Built-in Microwave Occupancy Detector | No                      |
| 1-10V Dimmable                        | On Request              |
| DALI Dimmable                         | On Request              |
| DMX 512 Compatible                    | No                      |