

**\*\*CLEARANCE\*\* Suspended Linear LED Light  
Up/Down Light 1200mm/4ft - Silver  
Anodised Aluminum (3,000lm) 32W Flicker  
Free**

~~£92.40~~ **£79.92**

## Product Description

**\*\*CLEARANCE\*\* Stock - limited quantities - check before ordering. Order entire amount required first time as once sold, no more will be available as a discontinued product. End of line stock from different batches, may be batch variation in colour between products. Better installed in single rooms rather than mixed in 1 room due to any variation.**

Suspended Linear LED Light for offices with both direct / indirect illumination. 1200mm / 4ft 32W Suspended Light for office, public open spaces and retail with high lumen output of 3,000 lumens in Natural White 4000K (2200lm:800lm uplight:downlight). Modern minimalist interior design highly suited by suspended luminaire. Finished in a choice of colours: stylish 6063 silver aluminum housing, enclosing an Frosted diffuser for subtle light output suiting a wide range of modern commercial and institutional applications, including hallways, retail & conference rooms. 1200mm linear design with a superior lumen output up to 2,900lm for ample lux levels across a range of environments - can be continuous with additional bracket. In-fils available on request. High CRI combined with stylish design make this unit perfectly suited to retail applications. Further options of dimmable: DALI and 1-10V.

DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE

## text\_attributes

### PRODUCT INFORMATION

|                  |                                   |
|------------------|-----------------------------------|
| LED Type         | SMD2835 LEDs                      |
| Warranty         | No warranty on clearance products |
| Part L Compliant | Yes                               |
| Dimensions       | 1178mm x 90mm x 67mm              |
| Weight           | 3.00kg                            |
| Equivalent to    | 2 x 36W T8                        |

## TECHNICAL SPECIFICATIONS

|                       |               |
|-----------------------|---------------|
| Power Consumption     | 32W           |
| Input Voltage         | 110-280V AC   |
| Power Factor          | >0.95         |
| Operating Temperature | -20°C to 50°C |
| L70 Rated Lifetime    | +45,000hrs    |
| Ingress Protection    | IP21          |

## LUMEN PERFORMANCE

|                              |                                           |
|------------------------------|-------------------------------------------|
| Luminous Efficiency          | 95lm/W                                    |
| Beam Angle                   | 120°                                      |
| CRI (Colour Rendering Index) | >80Ra                                     |
| Lumen Output                 | 3,000lm (2,200lm:800lm downlight:uplight) |

## AVAILABLE OPTIONS

|                    |                            |
|--------------------|----------------------------|
| Colour Temperature | Natural White (4000-4500K) |
| 1-10V Dimmable     | Available Variant          |
| DALI Dimmable      | Available Variant          |
| DMX 512 Compatible | No                         |