

****CLEARANCE** Suspended Linear LED Light
Up/Down Light 1200mm/4ft - Silver
Anodised Aluminium (5,000lm) 52W Flicker
Free**

~~£92.40~~ **£79.92**

Product Description

****CLEARANCE** Stock - limited quantities - check before ordering. Order entire amount required first time as once sold, no more will be available as a discontinued product. End of line stock from different batches, may be batch variation in colour between products. Better installed in single rooms rather than mixed in 1 room due to any variation.**

Suspended Linear LED Light for offices with both direct / indirect illumination. 1200mm / 4ft 40W Suspended Light for office, public open spaces and retail with high lumen output of 3,000 lumens in Natural White 4000K (2200lm:800lm uplight:downlight). Modern minimalist interior design highly suited by suspended luminaire. Finished in a choice of colours: stylish 6063 silver aluminum housing, enclosing an Frosted diffuser for subtle light output suiting a wide range of modern commercial and institutional applications, including hallways, retail & conference rooms. 1200mm linear design with a superior lumen output up to 2,900lm for ample lux levels across a range of environments - can be continuous with additional bracket. In-fils available on request. High CRI combined with stylish design make this unit perfectly suited to retail applications. Further options of dimmable: DALI and 1-10V.

DOWNLOAD PRODUCT INSTALLATION MANUAL / GUIDE

text_attributes

PRODUCT INFORMATION

LED Type	SMD2835 LEDs
Warranty	No warranty on clearance products
Part L Compliant	Yes
Dimensions	1178mm x 90mm x 67mm
Weight	3.00kg
Equivalent to	2 x 36W T8

TECHNICAL SPECIFICATIONS

Power Consumption	52W
Input Voltage	110-280V AC
Power Factor	>0.95
Operating Temperature	-20°C to 50°C
L70 Rated Lifetime	+45,000hrs
Ingress Protection	IP21

LUMEN PERFORMANCE

Luminous Efficiency	95lm/W
Beam Angle	120°
CRI (Colour Rendering Index)	>80Ra
Lumen Output	5000lm

AVAILABLE OPTIONS

Colour Temperature	Natural White (4000-4500K)
1-10V Dimmable	Available Variant
DALI Dimmable	Available Variant
DMX 512 Compatible	No